

**K 718 BASE**  
**K 718 PLUS**



K\_plus

K\_base



|  mm |  mm |  mm |  kg/m |  m |
|--|--|--|--|---|
| 260  |  | 20,5   | 5,96   |   |
| 270  |  | 20,5   | 6,13   |   |
| 280  |  | 20,5   |  |   |



**BESCHREIBUNG**

- Antriebsbereifung von LKW für beste Übertragung der Traktionskräfte
- Gute Eigenkühlung
- Ganzjahresreifen mit guten Wintereigenschaften
- Hervorragendes Ablaufbild durch häufige Unterbrechungen der Profilblöcke mit Lamellen und einer speziell auf dieses Profil abgestimmten Laufflächenmischung
- Höchste Laufleistung im Fernverkehr durch Einsatz der speziellen K\_plus Mischung und großer Profilaufstandsfläche
- Umweltfreundlich unterwegs durch geringen Treibstoffverbrauch und geringe CO<sub>2</sub>- und Geräuschemissionen
- Gute Haftung auf nasser Fahrbahn und auf winterlichen Straßen
- Optimale Leistung in Kombination mit dem Trailerprofil K 818

**FEATURES**

- Traction pattern guarantees optimum transmission of traction forces
- Good self-cooling
- All-season pattern with good winter properties
- Excellent tread wear due to frequent interruption of the blocks with sipes and a compound specially adapted for this tread pattern
- Maximum mileage in long-distance traffic by use of the special K\_plus compound and a large tread contact surface
- Environmentally friendly on the road thanks to low fuel consumption and low CO<sub>2</sub> and noise emissions
- Good adherence on wet roadways and winter roads
- Optimum performance in combination with the trailer tread K 818